

# Operating

# „Vacation block“

# Feedback



# Post-Boss

## 1 Empty mailbox



- Empty mailbox.
- The "Post Boss" is activated for the next mail delivery.

## 2 New mail delivery



- New mail delivery by the mail carrier.
- The "Post-Boss" display folds out automatically.

## 3 Activating the display



- Press the display with one finger in the letter slot and close the front flap.
- The "Post-Boss" is now activated again for the next display.

## Activate "vacation block"

- If you do not want the display to fold out during a longer period of absence (e.g., a long vacation), use the "vacation lock."
- To do this, press the display panel at the side edges into the holder with both thumbs



## Deactivate „vacation block“

Simply pull the display panel out of its lock with your finger.



## Thank you very much for your feedback.



We hope that the Post-Boss reliably makes your everyday life easier.

Please share your experiences on social media and on your purchasing platform.



The 'Post-Boss' has not yet convinced you.

Then please write us please your challenge:  
[feedback@post-boss.eu](mailto:feedback@post-boss.eu)

We are sure to find a solution so that we can improve our service and the 'Post-Boss' for you.

## Installation & operating instructions

For your mailbox with front flap



## Video tutorials:



[www.post-boss.eu](http://www.post-boss.eu)

Made in Germany

# Preparation



SCAN ME

## Cleaning the bonding area



For optimum bonding, clean the installation surface in the mailbox of oil and dust.

## Trial placement




Remove the protective film from the mounting strip approx. 3 mm from both edges - use tweezers if necessary



### Installation position

Align the 'Post-Boss' parallel to the flap edge.

For a front flap with an inner bar, attach the adapter first (see right).



### Check closure

Before final installation, check the closure - mark the position with a pen if necessary.

# Installation

 - only with internal bar

## Front flap with internal bar

For the version with an internal bar, glue the supplied adapter to the bar. This enables flush installation.

### Installation position with inner bar

Remove the adapter from the product carrier, peel off the protective film from the mounting adhesive tape and position it parallel to the inner bar.



### Installation position with inner bar

Then attach the post detector to the adapter and inner bar using the mounting adhesive tape.



# Installation

 - with and without inner bar

## Permanent installation



Ideally, install between 5 and 25 °C, as the temperature affects the adhesive performance.

- Completely remove the protective film from the 3M mounting adhesive strip.



- Mount the 'Post-Boss' in the desired position.



- Press firmly on different parts of the post detector for 10 seconds to ensure a permanent hold.

# Individualisation

## Personalise your new post detector

Make the 'post boss' your 'post boss'.

### Motiv



Choose your favourite from the 8 designs provided.

Cut out the design and stick it onto the display area.

The colour of the sticker provided matches the colour of your 'Post-Boss'.



You can, of course, also use the post detector without a motif.

### Display size



Simply adjust the display area to the desired length with a pair of scissors.